

Product Sheet

Pop XL Silent

English Version



Index

3	Overview
4	Key features
5-6	General specifications
7	Package contents
	Additional information

Key features

- Accommodates E-ATX (up to 280 mm) / ATX / mATX / Mini ITX Motherboards
- Excellent noise reduction thanks to a closed front, a closed top, bitumen side panels and sound-damping foam
- Easily mounted tempered glass side panel lets you showcase your components (Pop XL Silent TG)
- Up to four HDDs and six SSDs (or three HDDs and five SSDs with one optical bay in use)
- Comes with four of our 120 mm Aspect fans
- Two neatly concealed 5.25" bays with storage drawer and magnetic cover
- Easy cable management with multiple tie-down points, pre-mounted velcro straps and convenient extra-large pass-through holes
- Front I/O comes with two 3.0 USB 5 Gb/s ports, Mic and headphone jacks
- Top panel can be removed for two additional fan placements
- Optional USB-C upgrade kit (available separately) adds a full speed USB Type-C front port
- Comes with three ultra-versatile storage trays, each supporting a 3.5" and a 2.5" drive simultaneously



General specifications

	Pop XL Silent TG	Pop XL Silent Solid
Dedicated 3.5" drive mounts	• 0	• 0
Dedicated 2.5" drive mounts	• 4 (2 included)	• 4 (2 included)
Combined 3.5/2.5" drive mounts	• 4 (3 Included)	• 4 (3 included)
5.25" drive mounts	• 2	• 2
Expansion slots	• 8	• 8
Motherboard compatibility	• E-ATX up to 280mm / ATX / mATX /Mini ITX	• E-ATX up to 280mm / ATX / mATX /Mini ITX
Power supply type	• ATX	• ATX
Front interface	• 2x USB 3.0*, Audio	• 2x USB 3.0*, Audio
Total fan mounts	• 6x 120 mm or 5x 140 mm	• 6x 120 mm or 5x 140 mm
Front fan	• 3x 120/ 2x 140 mm (3x Aspect 12 included)	• 3x 120/ 2x 140 mm (3x Aspect 12 included)
Top fan	• 2x 120/140 mm	• 2x 120/140 mm
Rear fan	• 1x 120/140 mm (1x Aspect 12 included)	• 1x 120/140 mm (1x Aspect 12 included)
Bottom fan	• N/A	• N/A
Dust filters	• Top (perforated plastic), PSU (nylon), Front side intake (perforated steel)	• Top (perforated plastic), PSU (nylon), Front side intake (perforated steel)

General specifications

	Pop XL Silent TG	Pop XL Silent Solid
Front radiator	• Up to 360 mm	• Up to 360 mm
Top radiator	• Up to 280 mm	• Up to 280 mm
Rear radiator	• Up to 140 mm	• Up to 140 mm
Bottom radiator	• N/A	• N/A
PSU max length	• 205 mm	• 205 mm
GPU max length	• 430 mm with front fan mounted	• 430 mm with front fan mounted
CPU cooler max height	• 185 mm	• 185 mm
Cable routing space	• 19 mm	• 19 mm
Cable routing grommets	• No	• No
Fixed velcro straps	• Yes, 2 pcs	• Yes, 2 pcs
Tool-less push-to-lock	• N/A	• N/A
Captive thumbscrews	• HDD brackets, SSD brackets, side panels	• HDD brackets, SSD brackets, side panels
Left side panel	• Tempered glass, Clear Tint, 3 mm	• Industrial sound dampened steel
Right side panel	• Industrial sound dampened steel	• Industrial sound dampened steel
Case dimensions (LxWxH)	• 522 x 230 x 520 mm	• 522 x 230 x 520 mm
Net weight	• 10.43 kg	• 10.42 kg
Package dimensions (LxWxH)	• 608 x 330 x 625 mm	• 608 x 330 x 625 mm
Gross weight	• 12.10 kg	• 12.09 kg

* USB 3.1 Gen 2 Type-C add-on available separately

Package contents

Pop XL Silent

- Pop XL Silent case
- Accessory bag
- User manual

Additional information

Product	SKU	EAN	UPC	JAN
Pop XL Silent Black Solid	FD-C-POSIX-01	7340172703143	843276103149	4537694286145
Pop XL Silent Black TG Clear Tint	FD-C-POSIX-02	7340172703150	843276103156	4537694286152